

# KTHS5

## Basic Information



Size	PR	SPEED RANGE	STANDARD RIM	INFLATION PRESSURE (KPA)	PATTERN DEPTH (MM)	LI	LOAD CAPACITY (KG)	
							SINGLE	DUAL
205/75R17.5	14	M	6.00	750	14	124/122	1600	1500
215/75R17.5	16	M	6.00	760	15	126/124	1650	1500
235/75R17.5	16	M	6.75	830	15	132/129	2000	1850
225/70R19.5	16	M	6.75	760	15	128/126	1800	1700
245/70R19.5	16	M	7.50	830	15	135/133	2180	2060
265/70R19.5	16	M	7.50	830	15	140/138	2500	2360
255/70R22.5	16	M	7.50	830	15	140/137	2500	2300
275/70R22.5	16	M	8.25	900	15	148/145	3150	2900
285/75R24.5	16	L	8.25	830	15	147/144	3070	2800
295/75R22.5	16	L	9.00	830	15	146/143	3000	2725
11R24.5	16	L	8.25	830	15	149/146	3250	3000
11R22.5	16	M	8.25	830	15	146/143	3000	2725

- Improved tread design, high wear resistance and eccentric wear resistance.
- Low rolling resistance, Less fuel consumption, good handling quality.



**KETER**