



L-2

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	10Km/h 单胎负荷 MAX LOADING KG
12.5/70-16TL	6PR	L-2	10.00	16.5	848	316	200	1410
15.5/60-18TL	8PR	L-2	13.00	18	937	404	220	2195
15.5-25TL	12PR	L-2	12.00/1.3	23.5	1275	395	400	5600
17.5-25TL	12PR	L-2	14.00/1.5	26	1330	410	350	6150
17.5-25TT	12PR	L-2	14.00/1.5	26	1330	410	350	6150
17.5-25TL	16PR	L-2	14.00/1.5	26	1330	410	480	7300
20.5-25TL	16PR	L-2	17.00/2.0	29.5	1490	520	350	8250
23.5-25TT	16PR	L-2	19.50/2.5	31.5	1615	595	300	9500
23.5-25TL	16PR	L-2	19.50/2.5	31.5	1615	595	300	9500

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	标准气压 RELEVANT PRESSURE KPA	40Km/h 单胎负荷 MAX LOADING KG
13.00-24TL	16PR	L-2	9.00DC	23.5	1300	350	400	3200
13.00-24TL	12PR	L-2	9.00DC	23.5	1300	350	300	2725
14.00-24TL	16PR	L-2	9.00DC	25	1370	375	350	3650
14.00-24TT	16PR	L-2	9.00DC	25	1370	375	350	3650
14.00-24TL	12PR	L-2	9.00DC	25	1370	375	250	3075
15.5-25TL	16PR	L-2	12.00/1.3	23.5	1275	395	325	3750
17.5-25TL	20PR	L-2	14.00/1.5	26	1330	410	400	5000