

# 工程轮胎 OFF-THE-ROAD TYRE



NE3

规格 SIZE	层级 PR	花纹代码 PATTERN CODE	标准轮辋 STANDARD RIM	花纹深度 TREAD DEPTH MM	外直径 OVERALL DIAMETER MM	断面宽 SECTION WIDTH MM	50Km/h	
							标准气压 RELEVANT PRESSURE KPA	单胎负荷 MAX. LOADING KG
13.00-24 TT	18PR	NE3	10.00W	24	1301	351	450	3875
13.00-24 TL	18PR	NE3	10.00W	24	1301	351	450	3875
14.00-24 TT	24PR	NE3	10.00W	25.5	1368	375	575	5150
14.00-24 TL	24PR	NE3	10.00W	25.5	1368	375	575	5150
16.00-25 TL	32PR	NE3	11.25/2.0	28.5	1493	432	650	7300
17.5-25 TL	12PR	NE3	14.00/1.5	26	1350	445	225	3650
17.5-25 TT	12PR	NE3	14.00/1.5	26	1350	445	225	3650
17.5-25 TL	16PR	NE3	14.00/1.5	26	1350	445	300	4250
17.5-25 TT	16PR	NE3	14.00/1.5	26	1350	445	300	4250
20.5-25 TT	16PR	NE3	17.00/2.0	29	1490	520	275	5450
20.5-25 TL	16PR	NE3	17.00/2.0	29	1490	520	275	5450
20.5-25 TT	20PR	NE3	17.00/2.0	29	1490	520	325	6000
20.5-25 TL	20PR	NE3	17.00/2.0	29	1490	520	325	6000
23.5-25 TT	16PR	NE3	19.50/2.5	30	1615	595	225	6150
23.5-25 TL	16PR	NE3	19.50/2.5	30	1615	595	225	6150
23.5-25 TT	20PR	NE3	19.50/2.5	30	1615	595	300	7300
23.5-25 TL	20PR	NE3	19.50/2.5	30	1615	595	300	7300
26.5-25TL	28PR	NE3	22.00/3.0	35	1750	675	350	10000
29.5-25TL	28PR	NE3	25.00/3.5	38	1875	750	325	11500